

Display forward, reflected power and VSWR

2 GHz to 6 GHz

Diagnose 802.11a,b and g WLAN

Accessory:

Soft carrying bag with SMA 50 Ohm load 6 GHz, RPSMA male BN 86817.104 to SMA female Adaptor, SMA male to RPSMA, SMA male to SMA male Adaptor and special 2,4 GHz SMA Antenna



Specifications

Model No.:	86817.004
Frequency range:	2 – 6 GHz
Insertion loss:	<0.4dB
Absolute accuracy :	±1dB
Power range indicated:	1µW – 999mW
VSWR indicated:	1.01 – 9.99 : 1
Directivity:	>30dB
Peak Detect of:	<1mS pulse
Auto Power off	1 minute
Power Supply:	3Volt (2 X AAA Alkaline)
Max power consumption:	50 mA
Operating time (no backlight)	20 Hours
Optional Accessories:	SMA to RPSMA adaptors
Belt clip	Option
EMI/RFI	EN55022 /B
Dimensions:	– Width: 58 mm – Depth: 23 mm – Height: 105 mm
Weight incl. Batteries:	approx. 130g
Temperature:	– Operating 0 to 40°C – Storage –20 to 80°C
Colour:	– Standard White/Grey

Please contact for technical information and orders:
 SCHOMANDL-Vertriebs-GmbH
 Bahnhofstraße 108 · D-83224 Grassau/Germany
 Telephone: 08641-403-140 · Telefax: 08641-403-264
 e-mail: info@schomandl.de · Internet: http://www.schomandl.de